

A4000

Horn Speaker

Series horn speakers feature a double re-entrant metal horn with a high efficiency 15W compression driver to achieve clear and understandable voice paging and tone signaling in indoor and outdoor applications. These all-purpose units are ideal for use where an environmentally resistant speaker is specified for high intelligibility public address and signaling applications. These speakers are perfect for schools, recreational facilities, warehouses, distribution centers, parking facilities, and commercial buildings of all kinds. Assemblies are shipped complete with a screwdriver adjustable 25/70V transformer with protective cover and built-in strain relief, a universal swivel-style mounting bracket for easy and versatile installation, and a durable HSB epoxy finish for long service life.



FEATURES

- Type: Re-entrant horn
- Driver: Compression
- Power Rating: 15W continuous, 20W band ltd.
- Frequency: 475Hz - 4.5kHz
- Dispersion: 110
- Sensitivity (1W/ 1M): 121dB 4ft on axis @ 15W
- Impedances: 5000, 2500, 1300, 666, 333, 89, 45 Ohms
- Power Taps: 25V taps at .48, .94, 1.8, 7.5, 15W
70V taps at .9, 1.8, 3.8, 7.5, 15W
- Connections: Screw terminals with cover
- Dimensions: 8.5"Dia. X 9"H X 9.25"D
- Weight: 6lbs
- Mount: Equally spaced on 2.13" bolt circle

"MMTEB BOT TVCEB DIBOHFXE VPEPE"